


HEN







Bundle dimensions		1300 65	1600 65 75	1700 65 75	2000 65 75	2000	2200 [*]	2500 [*]
Tube sheet O.D.	mm	1300	1600	1700	2000	2000	2200	2500
Length	mm	6500	6500 7500	6500 7500	6500 7500	10000	7500 10000	10000 12500
Max lifting capacity 1		10 (15)	15 (22,5)	22 (33,3)	35 (52,5)	35 (52,5)	45 (67,5)	65 (97,5)


	Mef dimensions		1300 1600 65 65 75		THE PERSON NAMED IN	1700 2 65 75 65			The Person		2000 2200*)* 125	
	Width	1	mm	1600	2000		2050		2300		2300	2900	3050	
	Height	Н	mm	2000	2500		2600		2800		3000	3300	3500	
	Length	L	mm	7800	8100	9100	8100	9100	8100	9100	11600	9100 11600	11600 14	1100
	Height (motor)	Нм	mm	2150	2250		2250		2250		2250	2250	2250	
	Weight		Kg	4850	6200	6400	6500	6700	8250	8600	10800	12000 14000	16000 18	3500
**	Pulling max speed		m/min 2,5		2,5		2,5		2,0 50		2,0	2,0	1,5	
	Pulling force	g force 📛 T		20 3		30 35		50			65	90		

			100,700,000										
Bundle dimension	ns	1300	1600		1700		2000		2000	2200*		2500*	
		65	65	75	65	75	65	75	100	75	100	100	125
Tube sheet O.D. D	**	51	63		67		78		78	78 87		98	
Length	Ft	21	21	24	21	24	21	24	32	24	32	32	41
Max lifting capacity		22000 (33000)	33000	(49500)	48500	(72750)	77100	(115650)	77100 (115650)	99200	(148800)	143300	(214950)

Mef dim	Mef dimensions		ons 1300		1600 65 75		1700 65 75		00 75	2000	2200 [*]		2500 *	
Width	1	Ft	5.3	6.6		6.8		7.6		7.6	9.5		10.0	
Height	H	Ft	6.6	8.2		8.6		9.2		9.8	10,8		11.5	
Length	L	Ft	25.6	27	30	27	30	27	30	38	30	38	38	46.3
Height (motor) Нм	Ft	7.0	7	7.4		7.4		.4	7.4	7.4		7.4	
Weight		Lb	10700	13700	14100	14400	14800	18200	19000	23800	26500	30900	35300	40800
* Pulling max	Pulling max speed Ft/n		8.2	8.2		8.2		6.6		6.6 6.6		6.6	4.9	
Pulling force	Pulling force		44000	66100		77100		110200		110200 143300		3300	198400	

For heavyer bundles please contact us

* * With Diesel driving unit



Disassemblable rocker arm available






Aerial bundle extractors (on-shore)

Mef express


Standard supply

Diesel version

W Savedicon



Pneumatic version



Manual local command on back side



Electric Portable remote control




Pneumatic portable remote control



Lifting point alternative system



Main carriage for continuous pulling/pushing




Large base of rocker arm for balancing



New bundle supports with manual adjustement



Hydraulic vices for shell flange clamping



Two hydraulic cylinder for balancing action



Disassemblable rocker arm in 3 pieces for transport also by container



0



Mef express

Optionals

Removable Extension 1500 mm (4.92 Ft) long



Water cooled diesel engine

Portable wireless remote control Adapters for small diameter tube bundles

Hydraulically Bundle supports with cust. shape (buffle-rod bundle)









Stainless steel guards for sliding parts

Hydraulic telescopic extended arm for bundle insertion









Hydraulically controlled bundle supports





Aerial bundle extractors (on-shore)

